
Pavilion









BeyondIllumination

KIM lighting redefines the bollard by integrating the functionality of a NEMA rated Power Station. The Pavilion bollard can be tailored for any illumination requirement whether it be dark sky compliant, IES distributions or traditional low brightness optics. The body of the Pavilion bollard goes one step further than the hosting of receptacles and is fully compatible with any 1 or 2 gang device. A Bluetooth enabled RGBW luminous accent adds wayfinding capability. Rotational adjustment enables the square form factor to be installer friendly on winding landscape pathways.

A complete suite of sensors, controls, battery backup and audio system capability raises the bar on intelligent illumination.


Pavillon architectural illumination integration



Creative Illumination

Every site is unique and the lighting should echo the design intent of the architect or lighting designer. Pavilion can be configured with traditional elements or optimized LED optics to achieve the desired environmental illumination.

Styling configuration starts with 168 different combinations of the optic, top cap and body. Receptacle outlet capability adds the next level of customization. The RGBW luminous accent brings the final level of user personalization with a mobile device app for on-demand color changing.



DiscreteIllumination

Whether it be the timeless louver, diffused glow or open body, Pavilion can be configured for a wide range of applications.

Pavilion delivers IES distribution types with no glare at normal viewing angles.

The No Up-light, Clear Horizontal Lens and Clear Vertical Lens configurations are optimized for LED technology and deliver class-leading efficacy.

For architecture demanding more conventional styling, Pavilion can be configured with louvers, grilles or choice of a clear or a diffused vertical lenses for increased vertical illumination.



Integrated Illumination

Motion:

Pavilion's discrete sensor option intelligently detects occupancy for enhanced security, energy savings, and code compliance. Sensor operation reduces power by dimming light levels to 50%. When motion is detected the light level returns to full brightness.



SiteSync™:

SiteSync is a simple and affordable wireless control solution that offers the ability to reduce power consumption and maintenance costs while extending the life of the luminaire.

SiteSync




Pavilion is the industry's first bollard to incorporate RGBW color changing with Bluetooth connectivity. The RGBW luminous accent option is controlled wirelessly via Hubbell Lighting's Bluetooth® mobile app to dim or change color with Apple and Android devices.









Durable Illumination

All housing components are constructed with die-cast, low copper alloy (<0.6%) aluminum for superior durability. One piece silicone gasketing achieves an IP66 rated optical compartment and assures optical integrity. The finest stainless steel hardware is used to secure all components within the housing, providing durability in extreme weather conditions.








PAVILION 9

8 PAVILION



The Kim Lighting Theory of Relativity promotes harmony between outdoor lighting and architecture through a seamless blending of the two. Comprehensive product families allow specifiers to carry a continuous aesthetic through the project regardless of the application. As distance to structures decreases, luminaire height and scale decrease accordingly, maintaining visual comfort and contextual balance. This maximizes efficiency while preserving and enhancing the architectural experience.

Arm Mount 30 ft


Arm Mount 24 ft

Post top 12 ft

Wall Mount 9ft

Bollard 4ft





Night Time

Pavilion brings a timeless beauty and elegance to any environment. At KIM Lighting, we believe that architecture is experienced differently throughout the day and night, so we designed Pavilion to be the perfect balance of form and function.

Empowered Illumination

capable of hosting a multitude of receptacles, switches and devices. An integral outlet box can host any single or double gang device making it ideal for keypad, proximity card readers or actuator buttons at building entrances.


The tamper resistant NEMA 3R rated enclosure is ideal for applications needing GFCI or powered USB connectivity. In addition to electrical devices, Pavilion can also host a 3" speaker for PA system capability.

An emergency battery backup is available for all configurations to complete the package for a total

lighting solution.

KIM Lighting blurs the lines of bollard and power station functionality. The configurable body of Pavilion is







Pavilion Family





Ordering Information

MODEL TOP PA7R Pavilion Round PA7S Pavilion

Square

(PA7S only)

FT Flat Top PT Peaked Top **CT** Crowned Top (PA7R only)

CH Clear Horizontal Lens **CL** Clear Vertical Lens

LV Louvers GC Grille with clear lens

OPTICS

NU No Up-light

DL Diffuse Vertical Lens

GD Grille with diffuse lens

DISTRIBUTION

Type I 2 Type II

3 Type III 3HS Type III + House side shield

4 Type IV 5 Type V

LIGHT ENGINE

12L-010-5K7 14W (1000 lm 5000K), 70 CRI **12L-010-4K7** 14W (1000 lm 4000K), 70 CRI 12L-010-3K7 14W (1000 lm 3000K), 70 CRI **12L-010-AMB** 14W, Amber 590nm Monochromatic 12L-020-5K7 22W (2000 lm 5000K), 70 CRI **12L-020-4K7** 22W (2000 lm 4000K), 70 CRI 12L-020-3K7 22W (2000 lm 3000K), 70 CRI

12L-020-AMB 22W, Amber 590nm Monochromatic

BODY

24" OAH, Aluminum 24A 42" Aluminum Solid Body 42A 42" OAH., Brown Concrete 42" OAH., Natural Gray Concrete 42" OAH., Aluminum + Dual Receptacle Outlet Panel and Cover 42A/ROP-L 42" OAH., Aluminum + Dual

Receptacle Outlet Panel and Locking Cover **42A/2GEB** 42" OAH Aluminum + Integral

> Recessed 2-Gang Electrical Box 42" OAH Aluminum + Speaker Grille Enclosure for 3" Ø speaker

FINISH

BL Black DB Dark Bronze

GT Graphite

LG Light Gray PS Platinum Silver TT Titanium

WH White RAL RAL Color

CC Custom Color

CONTOLS

SWP SiteSync pre-commission MW Motion sensing (50% dim, 100% output upon

detection)

VOLTAGE

UNV 120-277V **120** 120V **277** 208-277V **347** 347V

480 480V

EM Battery backup (-20°C) LR Luminous Accent

OPTIONS

SF Single Fuse

DF Double Fuse

18 PAVILION PAVILION 19



ALERA LIGHTING

ARCHITECTURAL AREA LIGHTING

BEACON PRODUCTS

COLUMBIA LIGHTING

COMPASS

DUAL-LITE

HUBBELL CONTROL SOLUTIONS

HUBBELL INDUSTRIAL LIGHTING

HUBBELL OUTDOOR LIGHTING

KIM LIGHTING

KURT VERSEN

LITECONTROL

PRESCOLITE

WHITEWAY



17760 Rowland Street City of Industry, CA 91748 kimlighting.com

Kim-1001 9/14/17 Edition 1

Copyright © 2017 Kim Lighting, a division of Hubbell Lighting, Inc. All rights reserved. Please refer to online specifications for most up-to-date content as specifications are subject to change without notice.