

B-Flex

ARCHITECTURAL
LIGHTING

Ahead of the Curve

B-Flex Architectural Lighting
www.banvil2000.com

Banvil2000

B-Flex LIGHTING



1.5W / FT B-FLEX LED FLEXIBLE TAPE LIGHTING

Model	6000-BFL2835-1.5W24V-XX
Voltage:	24VDC
Length:	20Ft (6M) Reel, 32.8Ft (10M), 82Ft (25M) & 100Ft (30M) or Custom Cuts
Color Temp	2700K, 3500K, 4000K, 6000K (+- 5%), Red, Green or Blue
CRI	>90
Wattage	1.5 Watts/Ft / 4.8 Watts/M
Lumens	2700k - 134lm/Ft - 440lm/M 3500K - 145lm/Ft / 475lm/M 4000K - 170lm/Ft / 550lm/M 6000K - 178lm/Ft / 580lm/M
Beam Angle	120°
Dimming	0-10vDC Dimming / Triac / Low Voltage PWM Dimming
Construction	White PCB with Tesa® Tape Backing
LED	Epistar 2835
LED per	18 LEDs/ft / 60 LEDs/M
Warranty	5 Years

B-Flex architectural strip lights

- Bends and twists to follow any architectural line.
- Made with premium Epistar LED chips.
- Operates at low temperatures
- LED Flexible Tape Lighting is built to last
- Designed for interior and exterior use

2.25W / FT B-FLEX LED FLEXIBLE TAPE LIGHTING

Model	6010-BFL2835-2.25W24V-XX
Voltage:	24VDC
Length:	20Ft (6M) Reel, 32.8Ft (10M), 82Ft (25M) & 100Ft (30M) or Custom Cuts
Color Temp	2700K, 3500K, 4000K, 6000K (+- 5%), Red, Green or Blue
CRI	>90
Wattage	2.5 Watts/Ft / 7.2 Watts/M
Lumens	2700k - 122lm/Ft - 400lm/M 3500K - 130lm/Ft / 425lm/M 4000K - 147lm/Ft / 480lm/M 6000K - 175lm/Ft / 570lm/M
Beam Angle	120°
Dimming	0-10vDC Dimming / Triac / Low Voltage PWM Dimming
Construction	White PCB with Tesa® Tape Backing
LED	Epistar 2835
LED per	9 LEDs/ft / 30 LEDs/M
Warranty	5 Years



775 Main Street East, Milton ON
905.878.1080

Banvil2000

B-Flex architectural strip lights

- Bends and twists to follow any architectural line.
- Made with premium Epistar LED chips.
- Operates at low temperatures
- LED Flexible Tape Lighting is built to last
- Designed for interior and exterior use



2.25W/FT RGB B-FLEX LED FLEXIBLE TAPE LIGHTING

Model	6010-BFL2835-2.25W24V-RGB
Voltage:	24VDC
Length:	20Ft (6M) Reel, 32.8Ft (10M), 82Ft (25M) & 100Ft (30M) or Custom Cuts
Color Temp	100% mix of RGB
CRI	>90
Wattage	2.25 Watts/Ft / 7.2 Watts/M
Lumens	Red - 21 lm/Ft - 70 lm/M Green - 67 lm/Ft - 220 lm/M Blue - 12 lm/Ft - 40lm/M (Blue)
Beam Angle	120°
Dimming	Low Voltage PWM Dimming or DMX
Construction	White PCB with Tesa® Tape Backing
LED	Epistar 5060
IP Rating	IP43 or IP67
LED per	9 LEDs/ft - 30 LEDs/M
Warranty	5 Years

775 Main Street East, Milton ON
905.878.1080



B-Flex LIGHTING


3W/FT B-FLEX LED FLEXIBLE TAPE LIGHTING

Model	6020-BFL2835-1.5W24V-XX
Voltage:	24VDC
Length:	20Ft (6M) Reel, 32.8Ft (10M), 82Ft (25M) & 100Ft (30M) or Custom Cuts
Color Temp	2700K, 3500K, 4000K, 6000K (+- 5%), Red, Green or Blue
CRI	>90
Wattage	3 Watts/Ft / 9.6 Watts/M
Lumens	2700k - 260lm/Ft / 850lm/M 3500K - 280lm/Ft / 920lm/M 4000K - 323lm/Ft / 1060lm/M 6000K - 335lm/Ft / 1100lm/M
Beam Angle	120°
Dimming	0-10vDC Dimming / Triac / Low Voltage PWM Dimming
Construction	White PCB, Copper St with Tesa® Tape Backing
LED	Epistar 2835
IP Rating	IP43 or IP67
LED per	36 LEDs/ft / 120 LEDs/M
Warranty	5 Years



Banvil2000

B-Flex LIGHTING



4.5W/FT B-FLEX LED FLEXIBLE TAPE LIGHTING

Model	6030-BFL2835-4.5W24V-XX
Voltage:	24VDC
Length:	20Ft (6M) Reel, 32.8Ft (10M), 82Ft (25M) & 100Ft (30M) or Custom Cuts
Color Temp	2700K, 3500K, 4000K, 6000K (+- 5%), Red, Green or Blue
CRI	>90
Wattage	4.5 Watts/Ft / 14.4 Watts/M
Lumens	2700k - 244lm/Ft - 800lm/M 3500K - 302lm/Ft / 990lm/M 4000K - 338lm/Ft / 1110lm/M 6000K - 365lm/Ft / 1200lm/M
Beam Angle	120°
Dimming	Low Voltage PWM Dimming or DMX
Construction	White PCB with Tesa® Tape Backing
LED	Epistar 5060
IP Rating	IP43 or IP67
LED per	18 LEDs/ft - 60 LEDs/M
Warranty	5 Years

B-Flex architectural strip lights

- Bends and twists to follow any architectural line.
- Made with premium Epistar LED chips.
- Operates at low temperatures
- LED Flexible Tape Lighting is built to last
- Designed for interior and exterior use

4.5W/FT RGB B-FLEX LED FLEXIBLE TAPE LIGHTING

Model	6030-BFL-4.5W24V-RGB
Voltage:	24VDC
Length:	20Ft (6M) Reel, 32.8Ft (10M), 82Ft (25M) & 100Ft (30M) or Custom Cuts
Color Temp	100% mix of RGB
CRI	>90
Wattage	4.5 Watts/Ft - 14.4 Watts/M
Lumens	Red - 43 lm/Ft - 140 lm/M Green - 134 lm/Ft - 440 lm/M (Green) Blue - 24 lm/Ft - 80 lm/M
Beam Angle	120°
Dimming	Low Voltage PWM Dimming or DMX
Construction	White PCB with Tesa® Tape Backing
LED	Epistar 5060
IP Rating	IP43 or IP67
LED per	18 LEDs/ft - 60 LEDs/M
Warranty	5 Years



775 Main Street East, Milton ON
905.878.1080



Banvil2000

Model	PLG-4W120V
Voltage:	120V
Length:	164' Roll
Color Temp	2700K, 3000K, 4000K & 6000K
Wattage	4.5 Watts/Ft - 14.4 Watts/M
Lumens	115LM/W
LED	Epistar
IP Rating	IP65
Size	Width: .61" Thickness .22"
Warranty	3 Years


- Constant Current Design
- Plug & Play no external driver
- Over-Voltage Protection
- 164Ft Per Roll
- Minimum Cut Line of 4 inches
- IP65 Rated



120V ACCESSORIES



End Cap
Item #6500-EC-120V



End Cap with
2Ft (24") Power Cord Item
#6500-PC-HW-120V



End Cap with
2Ft (24") Power Plug Item
#6500-PC-PL-120V

CONNECTORS



Jumper 2Ft (24")
Item #6500-SPLConn-2ft-120V

MOUNTING ACCESSORIES



Mounting Clips
Item #6500-MC-120V




PVC Channel 1M
Item #6500-CHNL-PVC


ALUMINUM PROFILE EXTRUSIONS




Model: 6100-AP-LOW-1707
 Aluminium Low Profile
 Dimensions - 17.5mm x 7mm
 Max Length 78"
 Includes Clear or Diffused Lens




Model: 6100-AP-SQUARE-1612
 Slim Aluminium Recessed LED Profile
 Dimensions - 16mm x 12mm
 Max Length 78"
 Includes Clear or Diffused Lens




Model: 6100-AP-DOUBLE-2810
 Slim Aluminium Recessed LED Profile
 Dimensions - 20.8 mm x 10mm
 Max Length 78"
 Includes Clear or Diffused Lens




Model: 6100-AP-ANGLE-1919
 90 Degree Aluminium LED Profile
 Dimensions - 26.4mm x 19mm
 Max Length 78"
 Includes Clear or Diffused Lens





Model: 6100-AP-DOME-1715-30dg
 Aluminum Dome profile for narrow beam angle
 30 Degree
 Dimensions - 17.1mm x 13.4mm
 Max Length 78"
 Includes Clear or Diffused Lens



Model: 6100-AP-DOME-1715-60dg
 Aluminium Dome for 60 Degree Profile
 60 Degree
 Dimensions - 17.1mm x 13.4mm
 Max Length 78"
 Includes Clear or Diffused Lens



Model: 6100-AP-TAPERED-1715
 Aluminium Tapered Profile
 Dimensions - 17.5mm x 15mm
 Max Length 78"
 Includes Clear or Diffused Lens



Model: 6100-AP-RC-3535D
 Aluminum Double Wide & Deep – Recessed
 Dimensions - 35mm x 33mm
 Max Length 78"
 Includes Clear or Diffused Lens

Related Products

RGB Connectors



Solder Tip to SNAP
 Connector
 Item #8240-SNP-
 LVT-4C-10mm 4 Pin
 10mm RGB

Available in IP43 or IP67



FC to SNAP Connector Item
 #8240-SNP-FC-M-
 4C-10mm
 Male End
 4 Pin 10mm
 RGB

Available in IP43 or IP67



FC to SNAP Connector
 Item #8240-SNP-FC-F-
 4C-10mm
 Female
 4 Pin 10mm
 RGB

Available in IP43 or IP67

775 Main Street East, Milton ON
 905.878.1080

Banvil2000



2 Wire 8mm Male Snap Connector

Product Number	8220-SNP-FC-M-2C-8mm-XX	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	2 Pins	Strip Light Width 8mm
Male Connector	Single Color	IP43 or IP67



2 Wire 8mm Female Snap Connector

Product Number	8220-SNP-FC-F-2C-8mm-XX	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	2 Pins	Strip Light Width 8mm
Female Connector	Single Color	IP43 or IP67



2 Wire 8mm Bare End Snap Connector

Product Number	8220-SNP-IVF-2C-8mm-1ft	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	2 Pins	Strip Light Width 8mm
Bare End Connector	Single Color	IP43 or IP67



2 Wire 10mm Male Snap Connector

Product Number	8230-SNP-FC-M-2C-10mm	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	2 Pins	Strip Light Width 10mm
Male Connector	Single Color	IP43 or IP67



2 Wire 10mm Female Snap Connector

Product Number	8230-SNP-FC-F-2C-10mm	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	2 Pins	Strip Light Width 10mm
Female Connector	Single Color	IP43 or IP67



2 Wire 10mm Bare End Snap Connector

Product Number	8220-SNP-IVF-2C-10mm-1ft	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	2 Pins	Strip Light Width 10mm
Bare End Connector	Single Color	IP43 or IP67



4 Wire 10mm Male Snap Connector

Product Number	8240-SNP-FC-M-4C-10mm-XX	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	4 Pins	Strip Light Width 10mm
Male Connector	RGB Color	IP43 or IP67



4 Wire 10mm Female Snap Connector

Product Number	8240-SNP-FC-F-4C-10mm-XX	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	4 Pins	Strip Light Width 10mm
Female Connector	RGB Color	IP43 or IP67



4 Wire 10mm Bare End Snap Connector

Product Number	8240-SNP-IVF-4C-10mm-1ft	
Voltage & Current	DC3~24V / Max.5A	
Pin Quantity	4 Pins	Strip Light Width 10mm
Bare End Connector	RGB Color	IP43 or IP67



Male to Raw Wire Barrel Connectors

Product Numbers	8100-FC-M-2C-4in (4")	8100-FC-M-2C-1ft (12")
Type	FC-Male Connector	
Voltage Range	1-24V	
Amps	6 Amps Maximum	
Lengths	4" or 12"	
Measurements	Connector 1.75"L x .3"Dia	



Female to Raw Wire Barrel Connectors

Product Number	8100-FC-F-2C-4in (4")	8100-FC-F-2C-1ft (12")
Type	FC-Female Socket	
Voltage Range	1-24V	
Amps	6 Amps Maximum	
Lengths	4" or 12"	
Measurements	Connector 12.3"L x .4"Dia	



Male to Female Extension Barrel Connector Cables

Product Number	8110-FC-EXT-2C-XX	
Type	Extension Cables	
Voltage Range	1-24V	
Amps	6 Amps Maximum	
Lengths	1.5ft, 3ft, 6ft 10ft, or 16ft	
Measurements	M- 1.75"L x .3"Dia	F - 12.3"L x .4"Dia



Barrel Connector Splitter Cable

Product Number	8120-FC-2Y (2-Way)	8120-FC-6Y (6-Way)
Type	Available in 2-way or 6-way Splitters	
Voltage Range	1-24V	
Amps	6 Amps Maximum	
Socket	Female Socket Inlet	



Male to Female RGB Extension Barrel Connector Cables

Product Number	8150-FC-EXT-4C-XX	
Type	RGB Extension Cables	
Voltage Range	1-24V	
Amps	6 Amps Maximum	
Lengths	3ft and 10ft	



6-Way RGB Barrel Connector Splitter Cables

Product Number	8120-FC6Y-24V10A-4C-1.5ft (6-Way)	
Type	RGB 6-way Splitter	
Voltage Range	1-24V	
Amps	6 Amps Maximum	



Male Solder Tip 4 Wire RGB FC Connectors

Product Number	8150-FC-M-4C	
Voltage Range	1-24V	
Amps	6 Amps Maximum	
For RGB Flexible Strip Lighting Only		



Female Solder Tip 4 Wire RGB FC Connectors

Product Number	8150-FC-F-4C	
Voltage Range	1-24V	
Amps	6 Amps Maximum	
For RGB Flexible Strip Lighting Only		



20 Watt Power Supply

Product Number 5000-PSU-20W24V
 Wattage: 20W Voltage: 12V or 24V DC
 DC Power Supply With Prism FC Connector
 UL Certified Class II



60 Watt Power Supply

Product Number 5000-PSU-60W24V
 Wattage: 60W Voltage: 12V or 24V DC
 DC Power Supply With Prism FC Connector
 UL Certified Class II



90 Watt Power Supply

Product Number 5000-PSU-90W24V
 Wattage: 90W Voltage: 12V or 24V DC
 DC Power Supply With Prism FC Connector
 UL Certified Class II



Non-Dimming Power Supply

Product Number	5160-PSU-80W24V	5160-PSU-100W24V
Constant Voltage	90-277Vac	Class II
Wattage: 80W or 100W	Voltage: 24Vdc	
Non Dimming	IP67	
5yr Warranty	UL Recognized	



0-10V Dimming Power Supply

Product Number	5150-PSU-100W24V-CV-0-10VD	
Constant Voltage	LP Type	Class II
Wattage: 100W	Voltage: 24Vdc	
0-10V Dimming		
5yr Warranty	UL Listed	



TRIAC Dimming Power Supply

Product Number	5182-E75L24DC (75W)	5183-E96L24DC (96W)
Constant Voltage	120VAC	Class II
Wattage: 75W or 96W	Voltage: 24Vdc	
TRIAC Dimming	Electronic Dimmable LED Driver	
5yr Warranty	UL Listed	



M Series LED Dimming Controller

Product Number	8000-CTRL-D
PLG-M1 Dimming Remote	
Working Voltage	3Vdc
Working Frequency	433.92MHz
Remote Distance	100ft (30M)




M Series LED Color Temperature Controller

Product Number	8000-CTRL-CT
PLG-M2 Color Temperature Adjust Remote	
Working Voltage	3Vdc
Working Frequency	433.92MHz
Remote Distance	100ft (30M)



M Series LED RGB Controller

Product Number	8000-CTRL-RGB
PLG- M3 RGB Remote	
Working Voltage	3Vdc
Working Frequency	433.92MHz
Remote Distance	100ft (30M)



B-Flex
ARCHITECTURAL
LIGHTING
Ahead of the Curve

B-Flex Architectural Lighting
Ahead of the curve

Banvil2000